

3
LAURENS QUADRANGLE
227 - IOWA

FEET

LINE 1 (Cont'd)

HAVELOCK QUAD. - 226

8 74 12.7 UE; center of crossroad (Iowa 10 E.-W.), cor. secs. 27, 28, 33 and 34, T. 93 N., R. 33 W.; X-mark inside painted square, painted "UE Centerline" 1260.50

LINE 2

J. H. Tyndale, 1968; Book CV-2324

LAURENS QUAD. - 227

11 1 0.0 At Laurens, S. of the Chicago, Milwaukee, St. Paul & Pacific RR. station, in the city park, in the concrete wall of the S. basement steps of the public library 14.6 ft N. of the SE. cor. of the building, 1.5 ft S. of the S. side of the E. entrance, and about 0.8 ft above ground; a standard disk, stamped "LAURENS 1934" 1311.999

1 1.4 UE; 3 ft N., 42 ft E. and 2.7 ft lower than T-rd. W., cor. secs. 15, 16, 21 and 22, T. 93 N., R. 34 W.; N. side power pole; rail spike, painted "UE" 1305.35

2 2.4 UE; 40 ft N., 44 ft E. and 0.6 ft higher than crossroad, cor. secs. 9, 10, 15 and 16, T. 93 N., R. 34 W.; S. side power brace pole; rail spike, painted "UE" 1305.63

3 3.4 Reference mark, 378 ft S. of tablet; 55 ft S., and 28 ft W. of crossroad; 1.5 ft concrete tile culvert; chiseled square, painted "RM" 1320.00

4 3.5 Laurens, 3.25 mi N. and 0.5 mi W. of; 323 ft N., 49 ft W. and 2.5 ft lower than crossroad, cor. secs. 3, 4, 9 and 10, T. 93 N., R. 34 W.; 8 ft S. of steel witness sign; 1 ft E. of W. right-of-way fence; on 10 ft copper coated steel rod inside 6 in. concrete tile; standard tablet stamped "73 T 1968 1323" 1323.416

5 4.6 UE; 35 ft S., 44 ft E. and 5.2 ft lower than crossroad, cor. secs. 33, 34, 3 and 4, Tps. 93 and 94 N., R. 34 W.; N. side telephone pole; rail spike; painted "UE" 1326.83

6 5.6 UE; 34 ft S., 34 ft E. and 1.4 ft lower than crossroad, cor. secs. 27, 28, 33 and 34, T. 94 N., R. 34 W.; W. side power pole; rail spike, painted "UE" 1330.56

7 6.7 Reference mark, 175 ft NE. of tablet; 20 ft S., 109 ft E. of T-rd. E., 2.0 ft concrete tile culvert; chiseled square, painted "RM" 1330.95

8 6.7 Laurens, 6.25 mi N. and 0.5 mi W. of; 95 ft S., 46 ft W. and 0.3 ft higher than T-rd. E., cor. secs. 21, 22, 27 and 28, T. 94 N., R. 34 W.; 1 ft E. of W. right-of-way fence; on 10 ft copper coated steel rod inside 6 in. concrete tile; standard tablet stamped "74 T 1968 1335" 1334.777

9 7.9 UE; center of T-rd. S., +500 ft E. of E. sixteenth cor. secs. 16 and 21, T. 94 N., R. 34 W.; painted "UE Centerline" 1333.9

10 8.1 UE; 34 ft S., 230 ft E. and 3.3 ft lower than T-rd. N., cor. secs. 15, 16, 21 and 22, T. 94 N., R. 34 W.; W. end 1.5 ft concrete tile drive culvert; chiseled square, painted "UE" 1332.84

11 9.2 UE; 42 ft S., 31 ft E. and 4.0 ft lower than crossroad, cor. secs. 9, 10, 15 and 16, T. 94 N., R. 34 W.; N. side telephone pole; rail spike, painted "UE" 1337.74

12 10.3 Laurens, 9.25 mi N. and 0.5 mi W. of; 190 ft S., 40 ft W. and 2.7 ft lower than crossroad, cor. secs. 3, 4, 9 and 10, T. 94 N., R. 34 W.; 1 ft E. of W. right-of-way fence, on 10 ft copper coated steel rod inside 6 in. concrete tile; standard tablet stamped "75 T 1968 1346" 1346.004