## 2014 Franklin County, Iowa

Horizontal Datum: **NAD 83(2011)** - Vertical Datum: **NAVD 1988** lowa North Zone (1401)

Iowa Regional Coordinate System Zone 4 Sioux City-Iowa Falls US Survey Feet

Point Name: 25

NAD 83(2011) Latitude: **N42 °38'42.29683"** Longitude: **W93 °15'41.66360"** 

NAVD 88 Ortho Height: 1261.318sft Ellip. Ht: 1165.341sft Geoid12A


Mapping Angle: 0°09'42" Combination Scale Factor: 0.9998898471

lowa North Zone (1401) Northing: **3698218.363**sft Easting: **4985396.792**sft

laRCS Zone 4 Northing: **8644650.190**sft Easting: **14922888.544**sft

Designation: FRANKLIN CO. GPS CONTROL PT. 2004-25

**Monument Type**: Berntsen Top Security Rod Monument with a 2-1/2" dia. domed cap and a permanent magnet encased is a 5" dia. PVC pipe with a NGS style aluminum access cover.



## Franklin County, Iowa

Iowa North Zone (1401) Horiz. Datum: NAD83(1996) Vert. Datum: NAVD 1988 US Survey Feet 2004

Point Name: 025

Northing: **3698218.33**sft Easting: **4985396.78**sft

Orthometric Height: 1261.32sft


Ellipsoid Height: 1165.44sft

Latitude: 42°38'42.296"N Longitude: 93°15'41.664"W

Mapping Angle: 0°09'42" Combination Scale Factor: 0.999889840

Designation: FRANKLIN CO. GPS CONTROL PT. 2004-025

**Monument Type:** Berntsen Top Security Rod Monument with a 2-1/2" dia. domed cap and a permanent magnet encased is a 5" dia. PVC pipe with a NGS style aluminum access cover.



This document was prepared by Dan Corbin and Gary Brown for use by Franklin County, Iowa.