

LAND CORNERS AND HORIZONTAL CONTROL POINTS

DATE 3-6-90 M. J. HARDEN ASSOC., INC. A.P.I. JOB NO _____

Note: *Could be under Concrete* M.J.H. JOB NO. 6905-000

POINT NAME OR DESIGNATION GPS-8

POINT NO. _____, SEC. 7, T. 78, R. 25

ESTABLISHED BY: M.J. HARDEN Assoc. DATE: APRIL 1987

RECOVERED BY: _____ DATE: _____

COORDINATES: N 174379.952 (meters), E 475769.773 (meters)
572111.559, E 1560921.330
 (Iowa STATE PLANE COORDINATE SYSTEM, South ZONE)

COORDINATES: N _____, E _____
 (_____ STATE PLANE MODIFIED GRID COORDINATE SYSTEM _____ ZONE)

COORDINATES: N _____, E _____
 (INDEPENDENT GRID COORDINATE SYSTEM)

ELEVATION FACTOR _____ SCALE FACTOR _____

COMBINED ADJUSTMENT FACTOR _____

REF. PT.	AZIMUTH	DISTANCE	REFERENCES
No. 1	N.N.E.	86.67'	"X" NAILS IN NW FACE OF POWER POLE
No. 2	N.E.	37.73'	"X" NAILS IN TOP OF FENCE CORNER POST
No. 3	E.S.E.	91.73'	"X" NAILS IN S.W. FACE OF POWER POLE
No. 4	S.E.	71.10'	"X" NAILS IN N. FACE OF GATE POST
No. 5	S.S.E.	63.45'	"X" NAILS IN N. FACE OF GATE POST
No. 6	S.W.	59.40'	"X" NAILS IN S.E. FACE OF POWER POLE
No. 7	N.W.	112.27'	"X" NAILS IN N.E. FACE OF POWER POLE

DESCRIPTION

MARK: 3/8" PIPE

LOCATION: 10" BELOW GRAVEL SURFACE IN INTERSECTION OF 60TH ST. & DELAVAN DR.

SW. COR. 7-78-25

Note: John Adams Found Destroyed


